



BACKBONE

BACKBONE CONSTRUCTION LTD. - KISUMU, KENYA.

ITEM NO.	PICTURE	PRODUCT NAME	DESCRIPTION & FEATURES
150-DELUXE BH		MOTOR CYCLE	BRAND: LIFAN DOUBLE SHOCK INCLUDES: FULL HELMET & REFLECTIVE VEST LIGHT
250CC2H-WC BH		3 WHEELER (TUK TUK)	BRAND:LIFAN WATER COOLING INCLUDES :FULL HELMET &REFLECTIVE VEST LIGHT
CM350-4C TB		Tilting Drum Concrete Mixer	Drum Capacity: 350 L Mixing Capacity: 280 L Productivity: 4-5 m3/h Bags of Cement per Batch: 1 Bag Drum Rotation Speed: 25-30 rpm Upper Drum Thickness: 3 mm Bottom Drum Thickness: 4 mm Mixing Drum Size: $\phi 800 \times 900$ mm Tyre Size and Number: 4x(4.00-12) Engine Type: Air-cooled Diesel Engine 178FS(6HP) Total Weight: 295 kg Overall Size (Lx WxH): 1960x1200x1650 mm Packing Size (Lx WxH): 1860x860x1100 mm
CM400-4C TB		Tilting Drum Concrete Mixer	Drum Capacity: 400 L Mixing Capacity: 320 L Productivity: 5-6 m3/h Bags of Cement per Batch: 1 Bag Drum Rotation Speed: 25-30 rpm Upper Drum Thickness: 3 mm Bottom Drum Thickness: 4 mm Mixing Drum Size: $\phi 850 \times 900$ mm Tyre Size and Number: 4x(4.00-12) Engine Type: Air-cooled Diesel Engine 178FS(6HP) Total Weight: 315 kg Overall Size (Lx WxH): 2100x1200x1700 mm Packing Size (Lx WxH): 1960x960x1200 mm



BACKBONE

BACKBONE CONSTRUCTION LTD. - KISUMU, KENYA.

CM500-4D TB		Tilting Drum Concrete Mixer	Drum Capacity: 500 L Mixing Capacity: 400 L Productivity: 6-8 m³/h Bags of Cement per Batch: 1.5 Bag Drum Rotation Speed: 20-25 rpm Upper Drum Thickness: 3 mm Bottom Drum Thickness: 4 mm Mixing Drum Size: ϕ950x900 mm Tyre Size and Number: 4x(4.00-12) Engine Type: Water-cooled Diesel Engine R180 (8HP) Total Weight: 410 kg Overall Size (Lx WxH): 2160x1200x1750 mm Packing Size (Lx WxH): 2060x1060x1250 mm
JZC350-DH TB		Reversing Drum Concrete Mixer	Discharging Capacity: 350 L Loading Capacity: 560 L Productivity: 10-14 m³/h Bags of Cement per Batch: 2 Bag Drum Thickness: 6 mm Drum Size: ϕ1460x1850 mm Engine Type: Water-cooled Yanmar Diesel Engine CY1105 (18HP) Displace of Hydraulic Pump: 30mL/r Drum Rotation Speed: 14 rpm Power of Water Pump: 0.75 KW Max. Size of Aggregate: 60 mm Tyre Size: 6.50-16 Total Weight: 1800 kg Overall Size (Lx WxH): 3150x2400x3200 mm Packing Size (Lx WxH): 2200x2000x2500 mm
JZC350-EH TB		Reversing Drum Concrete Mixer (Yellow)	Discharging Capacity: 350 L Loading Capacity: 560 L Productivity: 10-14 m³/h Bags of Cement per Batch: 2 Bag Drum Thickness: 6 mm Drum Size: ϕ1460x1850 mm Mixing Motor Power: 5.5 KW Tipping Motor Power: 2.2 KW Water Pump Power: 0.55 KW Displace of Hydraulic Pump: 20mL/r Speed of Mixing Drum: 14 rpm Max. Size of Aggregate: 60 mm Tyre Size: 6.50-16 Total Weight: 1600 kg Voltage Standard: 380V, 50Hz, 3-Phase Overall Size (Lx WxH): 2850x2200x3200 mm Packing Size (Lx WxH): 2200x2000x2500 mm



BACKBONE

BACKBONE CONSTRUCTION LTD. - KISUMU, KENYA.

FCY15 TB		Hydraulic Site Dumper (Yellow)	Rated Payload: 1500 kg Rated Capacity of Bucket: 840 L Engine Type: Water-cooled Yanmar Diesel Engine CY1105(18HP) Tipping System: Hydraulic Engine Starting Model: Electric Started Structure of Main Model: Rigid Structure Transmission: 4x2, 3 forward gear, 1 reverse gear Max. Travel Speed: 24km/h Grade Ability: 25° Tyre Size: 7.50-16(Front), 5.00-16(Rear) Min Turning Radius: 3500 m Wheel Tread: 1260 mm Wheel Base: 1500 mm Total Weight: 1200 kg Overall Dimension: 2750x1500x2100 mm
AD		CONSTRUCTION HOIST	Capacity: 1000kg Made in Italy With Honda GX 270 engine Complete with stand-gantry and two bucket
AD			Capacity: 500kg Made in Italy With Honda GX 160 engine Complete with stand-gantry and two bucket
DML-0.5T TB		SMALL LIFTER	Rated Load: 500 kg Bucket Capacity: 120 L Rated Lifting Height: 25 m Arm Length: 2 m Engine Type: Loben Gasoline Engine (13HP) Max. Rotation Angle: 360° Starting Mode: Manually Total Weight: 160 kg Overall Size (LxWxH): 1700x1400x2400 mm
		TIRFOR	capacity:1.6ton wire rope size:11.2mm wire rope length: 30mtrs

YZS06H TB		WALK-behind VIBRATORY ROLLER	Operating Mass: 600 kg Vibration Drum Width: 600 mm Drum Diameter: $\phi 425$ mm Exciting Force: 20 KN Static Linear Load: 53 N/cm Engine Power: 5.5 HP Engine Type: 170FE, Air-cooled Diesel Engine Vibration Frequency: 70Hz Gradeability: 25% Fuel Tank Capacity: 21 L Travel Speed: 0-4 km/h Overall Size (LxWxH): 1450x1100x1200 mm
GQ-50 TB		REBAR CUTTER	Cutting Ability(Common Round Steel): $\phi 6-50$ mm Cutting Ability(Deformed Steel, Grade II): $\phi 8-40$ mm Speed: 28times/ min Electric Motor Power: 4KW Voltage Standard: 3-Phase, 380V, 50Hz Total Weight: 560 kg Overall Dimension (LxWxH) cm: 143x54x103
GW-50 TB		REBAR BENDER	Bending Ability(Common Round Steel): $\phi 6-50$ mm Bending Ability(Deformed Steel, Grade II): $\phi 6-42$ mm Max. Bending Speed: 14times/ min Electric Motor Power: 4KW Power Supply: 3-Phase, 380V, 50Hz Total Weight: 430 kg Overall Dimension (LxWxH) cm: 88x93x103
NM		MANUAL INTERLOCKING SOIL PRESS	



BACKBONE

BACKBONE CONSTRUCTION LTD. - KISUMU, KENYA.

ML 393 ST		MULTIPURPOSE WOOD WORKING MACHINE	Double Shaft 3HP 2850rpm 250 V 14 Amps
ML 393 ST			Single Shaft 3HP 2850rpm 250 V 14 Amps
MC 900 AD		WOOD LATHE	LIDA BRAND DISTANCE BETWEEN CENTRES: 900MM HEIGHT OF CENTRES :175MM MOTOR :220V/230V 50HZ 550W AMPS:2.4A R.M.P:1420 POWER:550W VOLTAGE 220V/230V HZ:50HZ POLS:4 PHASE :1 CLASS:B
MJ53435 AD		BANDSAW	LIDA BRAND CAPACITY (HXW): 150MMX350MM POWER VOLTAGE INPUT:220/230V POWER CURRENT OUTPUT:550W 50HZ
ST		PLATE COMPACTOR	Gasoline Plate Compactor Honda GX 160 Model: HZR110 Weight: 100 kg Output Power: 5.5 HP Frequency: 48 Hz Centrifugal Force: 15 KN Climbing Ability: ≤25° Advancing Speed: 20-30 m/min
T80 AD		PLATE COMPACTOR	Engine :3.8/5.0kw /HP Frequency :4200VPM centrifugal force :15kN Net Weight :92 KGS
T120 AD			Engine :5/5.5.kw /HP Frequency :5800VPM centrifugal force :19.8kN Net Weight :100kg

CN		POWER TROWEL	SIZE: 900MM 7.7HP PETROL ENGINE
AEW500S AD		ELECTRIC PRESSURE WASHER	AICO BRAND RATED PRESSURE: 3200PSI FLOW: 15LPM ELECTROMOTOR: 3.7kW R.P.M.: 2800RPM VOLTAGE: SINGLE PHASE 220V FREQUENCY: 50Hz PROTECTION LEVEL: IP 55 ALLOW TEMPERATURE: 0-60C°
MW		ELECTRIC HIGH PRESURE WASHER	FASA BRAND 150BAR MAX 2100W 450l/H 260EWBAR
LF2865 BH		GASOLINE HIGH PRESSURE WASHER	LIFAN BRAND PRESSURE: 2800 PSI POWER: 6.5HP GPM: 2.5 GASOLINE ENGINE
AMPW750 AD			Astramilano Rated Pressure: 2400PSI Permissible pressure: 2700PSI Rated Flow: 8.5LPM Max Flow: 9LPM Power: 7HP Rated Speed: 3400rpm Allowable temp: 0-60C°



BACKBONE

BACKBONE CONSTRUCTION LTD. - KISUMU, KENYA.

APW650 AD		GASOLINE HIGH PRESSURE WASHER	AICO brand Rated Pressure: 2600PSI Permissible pressure: 2900PSI Rated Flow: 8.5LPM Max Flow: 9LPM Power: 6.5HP Speed: 3400rpm Allowable temp: 0-60C° Rated
APW550 AD			AICO brand Rated Pressure: 2200PSI Permissible pressure: 2500PSI Rated Flow: 8.5LPM Max Flow: 9LPM Power: 5.5HP Speed: 3400rpm Allowable temp: 0-60C° Rated
CN		GENERATOR	Yamaha Brand 10KVA Single phase
CN			Yamaha Brand 6.5KVA single phase
TP		GENERATOR	Loncin Brand Rated power: 2.3KW max. power: 2.5 KW Rated Frequency: 50Hz Rated Volatge: 240v Rated current: 9.6A Weight: 44kg Manual start (3000w)
AG3000CLE AD			AICO BRAND RATED POWER(W):2300 RATED VOLTAGE (V):220 RATED CURRENT (A):10.5 RATED POWER FACTOR:1 MAXIMUM POWER:2500 RATED FREQUENCY (HZ): 50 PERFORMANCE GRADE G1 MAX AMBIENT TEMP40°C

AG2500CLE AD		GENERATOR	Brand: Aico Initial Current: less than 2.1A Cycle Use: 14.7 - 14.0V Standby Use: 13.5-13.8V
LF1200 BH			LIFAN BRAND RATED CURRENT:3.64A VOLTAGE: 220V FREQUENCY: 50HZ C.O.P:0.8KW 1KVA 4STROKE
LF8000E BH			LIFAN BRAND RATED CURRENT:31.8A VOLTAGE: 220V FREQUENCY: 50HZ RATED OUTPUT:7.0KW MAX OUTPUT:7.5KW PHASE :SINGLE
BH		DIESEL GENERATOR	POWERLINE BRAND WATER COOLED AC OUTPUT:12KW RPM:1500 PHASE:3 PF:0.8 FREQUENCY:50HZ AC AMP:16
MTHP50 MW		WATER PUMP	MITOYO BRAND SINGLE IMPELLER ENGINE TYPE:MT170F(7.0HP) MAX OUT PUT POWER:4.5KW/3600(R/MIN) MAX TORQUE: 12.4N.M/2500(R/MIN) DIAMETER OF INPUT PIPE :50MM(2") DIAMETER OF OUTPUT PIPE:50MM (2") LIFT:65M SUCTION HEAD:7M
MTHP50 MW			MITOYO BRAND SINGLE IMPELLER ENGINE TYPE:MT170F(7.0HP) MAX OUT PUT POWER:4.5KW/3600(R/MIN) MAX TORQUE: 12.4N.M/2500(R/MIN) DIAMETER OF INPUT PIPE :50MM(2") DIAMETER OF OUTPUT PIPE:50MM (2") LIFT:80M SUCTION HEAD:7M



BACKBONE

BACKBONE CONSTRUCTION LTD. - KISUMU, KENYA.

SCR-50HP AD			HONDA ENGINE CONNECTION DATA 50MM(2 INCH) MAX CAPACITY :520L/MIN (137GPW) MAX TOTAL HEAD:32MM (105FT) MAX SUCTION HEAD 8M (26FT) MAX OUTPUT (ROTATION):3.6KW (3600 RPM)
ACP30T AD		WATER PUMP	Max. Head: 25m Max. Capacity: 50m3/h Max Suction Head: 8m Altitude Height: ≤1000m Max Ambient: 313K Engine: 210 Rated speed: 3600rpm Displacement: 208cc
LF20HP BH			BRAND:LIFAN ENGINE MAX POWER: 6.5 HP 4.8KW SPEED ROTATION:3600RPM HEAD:50MM RATE OF FLOW:37.8M 3 /h PUMP LIFT:60M
TP		WATER PUMP	Loncin Water Pump Type: Centrifugal pump Inlet and Outlet 2" Gasoline: Petrol Engine: HP Net weight:: 23kg discharge head max: 23m suction head: 7m capacity max: 30m3/h rated speed : 3600min-1 water inlet diameter: 50mm water outlet diameter: 50mm
WP-20 CN		WATER PUMP	6.5HP Outlet Diameter 50: 2" Suction volume: 35m3/n Lift: 26m Suction length: 8m Matched power: 168F Required power/speed: 3.68kw/3600r/min
ML80 AD			Milano brand power: 6.5HP Dia: 76mm (3") Lift: 27 Operation: 3600rpm suction: 7m rated flow: 50m3/h

AMP50 AD		WATER PUMP	ASTRAMILANO BRAND POWER:5.5HP DIA:50MM(2") LIFT:27 OPERATION :3600RPM SUCTION:7M RATED FLOW:23M3/H
WP20 AD			Super Tiger Brand 5.5HP Dia: 50mm (2") Lift: 27 Operation: 3600rpm suction: 7m rated flow: 23m3/h
ML50 AD			Brand: Milano Power: 5.5HP Dia :50MM (2") Lift :27 Operation :3600RPM Suction:7M Rated flow: 23M3/H
KPM50 AD		WATER PUMP	Speroni brand Made in Italy 230v 50Hz 0.5HP Single phase 2850rpm P2 (kW) 0.37 P1(kW) 0.55 Q- 5-35 l/min - H.34-10m
CM32 AD			Speroni brand Made in Italy 230v 50Hz 1HP Single phase 2850rpm P2 (kW) 0.75 P1(kW) 1.2 Q- 10-125 l/min - H.29-14m



BACKBONE

BACKBONE CONSTRUCTION LTD. - KISUMU, KENYA.

AKCP180 AD		WATER PUMP SUBMERSIBLE PUMP	Qmax : 200 l/min Hmax : 60m Suct..Hmax: 9m Size: 1.5" X 1.25" 220V 50Hz 2850 Min KW 2.2 HP 3.0 IN 13A Max. W: 3000
QDX1.5-32-0.75A AD		WATER PUMP SUBMERSIBLE PUMP	AICO Brand Power:1HP voltage :220V Current:4.5A Phase :1~ Flow:1.5m 3/h head :32m Frequency: 50hz Insulation class:B Temp: water max:40° Speed :2850r/min IPX8 15M
QDX1.5-25-0.55A AD			AICO Brand Power:1HP voltage :220V Current:4.5A Phase :1~ Flow:1.5m 3/h head :32m frequency:50Hz insulation class:B Temp water max:40°C Speed :2850r/min IPX8 15M
IN		SUBMICIBLE PUMP	Made in India 1HP single Phase
IN			Made in India 2HP Single Phase
IN			Made in India 5HP 3Phase



BACKBONE

BACKBONE CONSTRUCTION LTD. - KISUMU, KENYA.

IN		CONTROL PANEL	Made in India 1HP single Phase
IN			Made in India 2HP Single Phase
IN			Made in India 5HP 3Phase
ST		WELDING MACHINE	150Amps Made in India Input Supply: 230 / 440 V Phase: 1 / 2 Frequency: 50Hz O.C.V: 60 V Current: 1.5 A Class: Class E Max. PRI. Insulation
ST			200Amps Made in India Input Supply: 230 / 440 V Phase: 1 / 2 Frequency: 50Hz Max. O.C.V: 60 V PRI. Current: 1.5 A Insulation Class: Class E Max. PRI. Insulation
ST			250Amps Made in India Input Supply: 230 / 440 V Phase: 1 / 2 Frequency: 50Hz Max. O.C.V: 60 V Current: 1.5 A Insulation Class: Class E Max. PRI. Insulation
ST			300Amps Made in India Input Supply: 230 / 440 V Phase: 1 / 2 Frequency: 50Hz Max. O.C.V: 60 V Current: 1.5 A Insulation Class: Class E Max. PRI. Insulation



BACKBONE

BACKBONE CONSTRUCTION LTD. - KISUMU, KENYA.

ST			400Amps Made in India Input Supply: 230 / 440 V Phase: 1 / 2 Frequency: 50Hz Max. O.C.V: 60 V PRI. Current: 1.5 A Insulation Class: Class E
BX1-250C1 AD		WELDING MACHINE	90A-23.6v~ 250A /30V 50Hz
BX1-200C1 AD			AICO brand 80A/23.6V ~200A/28V 50Hz
BX1-180C1 AD			AICO BRAND -50HZ UO=45-48V U1=230V
BX1-160C1 AD			AICO BRAND 60A/22.4V-160A/26.4
TLD-250B ST		SPARTEN WELDING MACHINE	Input Single Phase 240V
ST		PPR WELDING MACHINE	20-32mm 0 °C- 40°C 220 ±10% V >1 Mn 45-96% 200± °C <5MA
ST			20-63mm 0 °C- 40°C 220 ±10% V >1 Mn 45-95% 260± °C <5MA

ST		VIBRATOR	Petrol Engine Honda Model: GX 160 5.5 HP Power: N.W: 21.5 kg G.W: 22.5 kg Size: 51x38x45 cm
ST		VIBRATOR	Electric Vibrator Motor Model: ZN-G Voltage: 220 V Power: 1.5 KW Frequency: 50Hz
ZN-50 TB		ELECTRIC CONCRETE VIBRATOR	Diameter of Matched Vibrator Poker: $\phi 50$ mm Length of Matched Vibrator Poker: 6 mm Electric Motor Power: 1.5 KW Rated Current: 3.24 A Motor Rotating Speed: 2840 r/min Voltage: 380 V Frequency: 50Hz Gross Weight of Vibrator: 13 kg Gross Weight of Vibrator Poker: 20 kg Packing Size of Vibrator: 34x28x30 cm Packing Size of Vibrator Poker: 84x84x6 cm
AD/ST		POKER	Dynapac 45mmX6m
ZX28MM ST			28mm
CH		DEMOLITION BREAKER	220v 50/60Hz 2800w 2040r/min-1 65mm



BACKBONE

BACKBONE CONSTRUCTION LTD. - KISUMU, KENYA.

SWG-2A	AD		PIPE BENDER	AICO Brand Bending Angle: 90<0<180 Max Stroke(mm): 250mm Crimp Range(mm):1/2 - 2
21T-R2	AD		PIPE TREADING MACHINE	AICO Brand Electrical Capacity: 1/2 - 2"(Pipe) Motor: 750W 220V/50Hz Single Phase Spindle Speed: 28rpm
TC120242	VV		Air compressor TOTAL	Voltage:230V,50Hz Power: 1.5 kW (2 HP) Speed:2850rpm Tank:24L(6.3Gal) Work Pressure:8bar(116Psi) Transport handle Wheels for easy transport Base foot with vacuum cup function Drain cock Pressure controller Pressure gauge and quick coupling for regulated working pressure
ZB-0.14/8	MW		AIR COMPRESSOR	POWERPAK BRAND TANK: 50LTRS PRESSURE: 115 PSI POWER:3HP TANK:50L CAPACITY:140L/MIN VOLTAGE:230V FREQUENCY:50HZ
V-0.25/8	MW			POWERPAK BRAND TANK:100L PRESSURE:115 PSI POWER:3HP CAPACITY :250L/MIN VOLTAGE:230V FREQUENCY:50HZ

TC125502 VV		Air compressor TOTAL	Voltage:230V,50Hz Power: 1.8 kW (2.5 HP) Speed:2850rpm Tank:50L(13.2Gal) Work Pressure:8bar(116Psi) Transport handle Wheels for easy transport Base foot with vacuum cup function Drain cock Pressure controller Pressure gauge and quick coupling for regulated working pressure Intake filter Non-return valve Safety valve Pump lubricated with oil .
AC225D AD		AIR COMPRESSOR	AICO BRAND ELECTRIC PRESS 8 BAR 115PSI MOTAR 2.5HP 1.8KW TAP CAP 25LTRS
ML50B AD			MILANO BRAND ELECTRIC PRESS 8BAR 115PSI MOTOR 2 HP 1.5KW TANK CAP 50LTRS HEAD ϕ 51MM
ML50E AD			MILANO BRAND PETROL ENGINE PRESS 8BAR 115PSI 5.5HP TANK CAP 50LTRS HEAD ϕ 51MM
ML100B AD			MILANO BRAND ELECTRIC PRESS 8BAR 115PSI MOTOR 2 HP 1.5KW TANK CAP 100LTRS HEAD ϕ 51MM

ML100E AD			MILANO BRAND PETROL ENGINE PRESS 8BAR 115PSI 5.5HP TANK CAP 100LTRS HEAD ϕ 51MM
ML150B AD			MILANO BRAND ELECTRIC PRESS 8BAR 115PSI TANK CAP 150LTRS HEAD ϕ 65mm MOTOR 3HP 2.2KW
ML200B AD		AIR COMPRESSOR	MILANO BRAND ELECTRIC PRESS 8BAR 115PSI MOTOR 3HP 2.2KW TANK CAP 200LTRS HEAD ϕ 65MM
TTAC1401 VV		AUTO AIR COMPRESSOR TOTAL	Power supply:DC12V Max.pressure:140PSI(10Bar) Max.air flow:35L/min Rated current:10A 1.5M PU hose with Japanese style brass quick-releasing adapter 3M cord with cigarette lighter 2 battery clips 3pcs nozzle adapters.
MW		DIESEL ENGINE	POWERPAK BRAND 10HP 7.4KW 1500RPM
C400HD BH		ENGINE	BRAND:CARLTONS UK ENGINE:GASOLINE 13HP BOREXSTROKE:88X64MM MAX POWER IN THEORY:8.2KW/3600RPM POWER RECOMMENDED: 7.5KW/3600RPM
C290HD BH			BRAND:CARLTONS UK GASOLINE ENGINE 8.5HP



BACKBONE

BACKBONE CONSTRUCTION LTD. - KISUMU, KENYA.

ML200 AD		ENGINE	Milano brand 7.5HP
VS			Cigma Brand 7.5HP
YL112M-2 AD		MOTAR	AICO Brand Single Phase 2850r/min 5HP 3.7Kw 220-240V 50HZ22.1-20.3a
YL90L-4 AD			AICO Brand single phase 2hp 1.5kw 220-240v 9.44 - 8.65 A 1420 r/min
5010C TP		CUT OFF METAL MACHINE	Tosan Brand no 3750/min 220-230v 50Hz 2200w cutting depth: 120mm
QY-4355 CN			14" Cutting Diameter: 250mm 2400W 220V RPM 4000 50Hz
PT0935502 VV		ELECTRIC CUT OFF MACHINE PRESCOTT	Ratedvoltage:220-240V~50/60Hz Input Power: 2000W Blade Size: 355mm No-load Speed: 3800r/min Max. cutting capacity:58mm in solid steel pipe 110mm in hollow steel pipe 110x130mm in rectangle

TS42142101 VV		MITRE SAW TOTAL	Input power: 1400W No load speed:5000rpm Blade diameter:210mm Aluminum base Max. cutting capacity:55*120mm Positive stops at 9 settings right/left TCT blade for precision cutting Miter cuts 0-45° left and right Bevel cuts up to 45° to the left
TP		MORTAR SPRAYER	
ST		BLOCK/CABRO SPLITTER	Operation Mass: 48Kg Max. Cutting Height: 14cm Drive: Manual Blade Length:43cm
TBG15015 VV		BENCH GRINDER TOTAL	Input power:150W No load speed:2950rpm Wheel size:150 mm Adjustable work rest Including 1 set eye shield
GWS 22-230 +CB ST		ANGLE GRINDER Bosch Professional	Rated Power Input: 2,200W No –Load Speed: 6500 rpm Power Output: 380 W Grinding Spindle Thread: M 14 Disc Diameter: 230mm Weight: 5.3 kg
GWS 750-115+CB ST		ANGLE GRINDER Bosch Professional	Rated Power Input: 750W No –Load Speed: 11,000 rpm Power Output: 380 W Grinding Spindle Thread: M 14 Disc Diameter: 115mm Weight: 1.8 kg



BACKBONE

BACKBONE CONSTRUCTION LTD. - KISUMU, KENYA.

GWS 6700 ST		ANGLE GRINDER Bosch Professional	Rated Power Input: 670 W No –Load Speed: 12000 rpm Grinding Spindle Thread: M 14 Diameter: 115 mm 298 mm 77 mm Weight: 1.8 kg Disc Length: Width:
GA-7020 CN		GRINDER Makita	180mm 220v 10A 2100W RPM7700 50-60Hz
BDG2223 AD		GRINDER BLACK & DECKER	Type 01 220-240V 50/60Hz n 6500RPM 2200W M14 Ø230mm
DWE492 AD		GRINDER DEWALT	Made in India 220-204V 50/60Hz 2200W 80m/s Max n 6600/min M14 Ø230mm
PT0311508 VV		ANGLE GRINDER PRESCOTT	Rated voltage:220-240V~50/60Hz Input Power:1100w No-load Speed:11000r/min Disc Size:115mm
PT0323001 VV			9" Rated voltage:220-240V Input Power:2400W No-load Speed:6500r/min Disc Size:230mm
TG501032 VV		ELECTRIC MINI GRINDER	Input power:130W No load speed:10000-32000rpm Collet size:3.2mm Spindle lock for accessories change Variable speed for different work With 1 pcs flexible shaft Including 100pcs accessories Packed in blow mould case

TP1141806 VV		ANGLE POLISHER	Voltage: 220V-240V~50-60Hz Input power: 1400W No load speed: 900-3800rpm Disc diameter:180mm Durable aluminum gear box 1pcs polishing pad 1pcs polishing bonnet Packed by color box
ZQJ4113 AD		DRILL PRESS	LIDA BRAND CAPACITY :13MM 220V 50 HZ 240W POWER"250W RPM:1420 1.2A
ZQJ4116 AD			LIDA BRAND CAPACITY :16MM 220V 50HZ 375W POWER:375W RPM:1420
TDP133501 VV		DRILL PRESS TOTAL	Input power: 350W Spindle speed settings:5 No load speed: 580-2650 rpm Max drilling capacity:13mm Spindle travel:50mm Column diameter:46mm Table size:160*160 mm Base size:314*200mm Adjustable working table Net weight:19Kgs Machine height:590mm
PT0201302 VV		IMPACT DRILL PRESCOTT	voltage:220-240V~50/60Hz Drill Capacity:13mm Rated input power:810w No-load Speed: 3000r/min Metal 10mm/wood 25mm
PT0201601 VV			Metal 10mm/wood 25mm voltage:220-240V~50/60Hz Drill Capacity:16mm Rated input power:1100watts No-load Speed: 3000r/min Metal 13mm/wood 30mm ALUMINIUM GEAR BOX

GSB 16 RE ST		IMPACT DRILL Bosch Professional	Rated Power Input: 701 W Impact Rate at no-Load Speed: 0-48000 bpm Drill Spindle Connecting Thread: 1/2"-20 UNF Rated Speed: 0-1640 rpm Weight: 1.9 kg Chuck Type: Keyless Chuck Size: 13 mm
GSB 1300 ST		IMPACT DRILL Bosch Professional	Rated Power Input: 550W Impact Rate at no-Load Speed: 0-41600 bpm Drill Spindle Connecting Thread: 43 Weight: 1.8 kg Width: 253 mm Chuck Size: 13 mm
HP1630 CN		HAMMER DRILL Makita	3.4A 710W 50-60Hz Concrete: 16mm (5/8') Steel: 13mm (1/2') RPM 3200
GBH 2-24 DFR ST		ROTARY HAMMER with SDS -plus Bosch Professional	Rated Power Input: 790W Tool holder: SDS-plus Impact energy: 2,7 J Impact Rate at rated Speed: 0-4200 bpm Rated speed: 0-930 rpm Weight: 2.9 kg
GBH 2000 ST		ROTARY HAMMER with SDS -plus Bosch Professional	Rated Power Input: 600W Tool holder: SDS-plus Impact energy: 0-1.7 J Impact Rate at rated Speed: 0-4400bpm Rated speed: 0-1400 rpm Weight: 2.3 kg
HR2470F CN		ROTARY HAMMER Makita	Concrete: 24mm Steel: 13mm 220-230V 3.6A 50-60Hz 780W RPM 1100 RPM 4500



BACKBONE

BACKBONE CONSTRUCTION LTD. - KISUMU, KENYA.

KR604 AD		DRILL BLACK & DECKER	Type 3 600W Ø13mm 220-204V 50/60Hz 2800/min 0-
DWD-024 AD		DRILL DEWALT	220-240V 50-60Hz 750W 0-2800/min 13mm
PT0101007 VV		TORQUE ELECTRIC DRILL PRESCOTT	Voltage:220-240V~50/60Hz Drill Capacity:10mm Rated input power:280W No-load Speed: 750r/min Max Torque:21N.M Max Dia.of drilling: Metal 10mm/wood 20mm
GSR 1800-LI ST		CORDLESS DRILL/DRIVER Bosch Professional	Torque, max. (soft screwdriving applications): 24Nm Torque, max. (hard screwdriving applications): 18Nm No-load speed (1st gear/2nd gear): 0-400/0-1300- rpm Chuck clamping range: 0,8-10mm Battery voltage: 18V Weight incl. battery: 1.4kg Torque setting: 25+1 Max. drilling diameter in wood: 29mm Max. drilling diameter in steel: 10mm Max. screw diameter: 8mm
GSR 1440-LI ST		CORDLESS DRILL/DRIVER Bosch Professional	Torque, max. (soft screwdriving applications): 15Nm Torque, max. (hard screwdriving applications): 30Nm No-load speed (1st gear/2nd gear): 0-420/1400- rpm Chuck clamping range: 1-10mm Battery voltage: 14.4V Weight incl. battery: 1.3kg Torque setting: 25+1 Max. drilling diameter in wood: 25mm Max. drilling diameter in steel: 25mm Max. screw diameter: 7mm

GSR14,4-2 CN		CORDLESS DRILL/DRIVER Bosch Professional	Torque, max. (soft screwdriving applications): 15Nm Torque, max. (hard screwdriving applications): 30Nm No-load speed (1st gear/2nd gear): 0-400/0-1400-rpm Chuck clamping min/max: 1-10mm Battery voltage: 14.4V Weight incl. battery: 1.5kg Torque setting: 25+1 Max. drilling diameter in wood: 26mm Max. drilling diameter in steel: 12mm Max. screw diameter: 8mm
TD312106-8 VV		Cordless drill TOTAL	Drill volts:12V NO LOAD SPEED :0-550RPM CHUCK:10MM KEYLESS CHUCK TORQUE SETTINGS :15+1 LIGHT WEIGHT DESIGN INCLUDING 1 PCS BATTERY PACK INCLUDING 1 PCS 3-5HR CHARGER
CN		CORDLESS DRILL	10mm Forward & Reverse 21V RPM 0-600
PT2000401 VV		44 pcs Accessories CORDLESS SCREWDRIVER PRESCOTT	Ni-cd Voltage:4.8v No-load speed:180rpm Charge:5-7hour Chuck:6.35MM Battery:700mAh Output torque:3Nm Packed in BMC Case
272 XP ST		POWER SAW HUSQVARNA	

GKS 235 ST		HAND-HELD CIRCULAR SAW Bosch Professional	Rated Power Input: 2100 W Weight: 7.6 kg No-load speed: 5.000 rpm Saw blade bore diameter: 25.0 mm Saw blade diameter: 235 mm
GKS 190 ST		HAND-HELD CIRCULAR SAW Bosch Professional	Rated Power Input: 1400W Weight: 4.1 kg No-load speed: 5.500 rpm Saw blade bore diameter: 20.0 mm Saw blade diameter: 184 mm
5900B CN		CIRCULAR SAW Makita	235mm(9") 220V 8A 1400W 50-60Hz RPM4100
3612BR CN		ROTER MACHINE Makita	220V 7.7A 1600W 50-60Hz RPM 23000 12mm hole bit
PT1701201 VV		Electric Router PRESCOTT	Rated Voltage:220-240V~50-60Hz Input Power:1500W No-load speed:22000r/min Collecting Capacity:12mm/12.7mm. 6mm & 8mm Collets. 1 pc Spanner.
GDM 13-34 ST		MARBLE SAW Bosch Professional	Rated Power Input: 1300 W Weight: 2.8 kg No-load speed: 12.000 rpm Saw blade bore diameter: 20.0 mm
TS3141102 VV		MARBLE CUTTER TOTAL	Input power: 1400W No load speed: 0-11000rpm Dia of blade:110mm Max cutting capacity:34mm



BACKBONE

BACKBONE CONSTRUCTION LTD. - KISUMU, KENYA.

THT576004 VV		TILE CUTTER TOTAL	600mm Tile cutter 1.Max cutting length:600mm 2.Max cutting thickness : 12mm 3.Steel base size:815x195cm 4.Thickness of the base: 2mm 5.With 2 pcs Tungsten carbide blade Blade size : 16x6x3mm 6.Multi-function:direct line cutting, diagonal line cutting 7.Diameter of sliding bar:19mm Packed by carton box
GSS 2300 ST		ORBITAL SANDER Bosch Professional	Rated Power Input: 190 W Weight: 1.5 kg No-load orbital stroke rate: 0-24000 opm No-load speed: 0-12000 rpm Oscillating circuit diameter: 2 mm Sanding sheet for clamping, width: 93 mm Sanding sheet for clamping, length: 230
PT1562001 VV		ELECTRIC BELT SANDER PRESCOTT	Rated Voltage:220-240V~50-60Hz Input Power:1200W Sanding Speed:550r/min Belt Size:100x610mm Packed in Blow Moulded Case
PT1608201 VV		ELECTRIC PLANER PRESCOTT	Rated voltage:220-240V~50-60Hz Input Power:560W No-load speed 16000r/min Cutting Width:82x1mm
GST 65 BE ST		JIGSAW Bosch Professional	Rated Power Input: 400W Weight: 1.7 kg No-load stroke rate: 500-3100spm Cutting depth: 80 mm

TS205656 VV		Jig saw-570W TOTAL	Voltage: 220-240V~50Hz Input Power:570W No load speed:800-3000rpm Cutting capacity: Voltage: 220-240V~50Hz 65mm in wood 8mm in steel4 step pendulum function Packed in color box
TB2066 VV		ASPIRATOR BLOWER TOTAL	Input power:600W No load speed:0-16000rpm Max blowing rate:0-3.5m³/min Variable speed With 1pcs dust bag
GHG 500-2 ST		HEAT GUN Bosch Professional	Rated Power Input: 1600W Weight: 0.8 kg Length: 255mm Height: 255mm
KX1650 AD		HEAT GUN BLACK & DECKER	Type 01 220-240V 50/60Hz 1750W
PT1925002+ VV		HEAT GUN PRESCOTT	Rated Voltage:220-240V~50-60Hz Input Power:2000W Temperature: I :450°C II :600°C Air Flow: I :300L/M II :500L/M
TAT81501 VV		2 IN 1 Nailers & Stapler TOTAL	Operation pressure: 4-7Mpa(60-100Psi) Magazine capacity:100Pcs Brad size:15-50mm Ga18,1.25X1.0mm Staple size:16-40mm Ga18,1.25X1.0mm Staple crown:5.7mm Including 1000pcs brad nails+1000pcs staples


PT3003002 VV		ELECTRIC STAPLE GUN 2 IN 1 PRESCOTT	Rated Voltage:220-240V~50-60Hz Rated Current:9A Rated Filing Speed:≤20pcs/min Staple Spec.:Type 60018G L=15-20mm Brad Nail Spec.: Type F 18g L=15-32mm Nail QTY:100pcs Rated
PT2750002+ VV		ELECTRIC SPRAY GUN PRESCOTT	Rated Voltage:220-240V~50-60Hz Rated Input Power:100W Nozzle size:0.8mm Max. Viscosity:50DIN-s Max. Spraying Pressure:140Bar Flow rate:300ml/min Container Capacity: 700ml
PAT01W71G VV		400cc Spray Gun TOTAL	Standard nozzle:1.5mm Operating pressure:3-4bar Pattern width:180-250mm Air cons:4.2-7.1cfm(119-200l/min) Paint capacity:400ccSuitable for base coat
CB-30P VV		BATTERY CHARGER PRESCOTT	Rated Input:220-240v-50/60hz rated capacity:450w. 12V/24V. Max. 220 AMPS
TT101111 VV		Glue gun	Voltage: 220-240V~50Hz Input power:100W Gluing capacity : 10-15g/min Glue stick diameter:11.2mm Ideal for adhesive attachment, model making, repairing, sealing and jointing Mechanical feed system for sensitive metering and rapid application Including 2pcs 11.2mm glue sticks Packed in double blister

GOL 32 D ST		OPTICAL LEVEL Bosch Professional	Length: 215 mm Height: 145 mm Width: 135 mm Accuracy: 1 mm at 30 m Dust and splash protection: IP 54 Weight, approx.: 1.5 kg Tripod thread: 5/8" Unit of measure: 360 degrees Magnification : 32 x Scope of supply: adjusting pin, allen key, lens cover, plumb bob, BT 160 professional tripod and GR 500 levelling staff.
CN		DUMPY LEVEL	with stand
CN		LINE LASER MACHINE	Colour red with stand
CN			colour green with stand
CN		THEODOLITE	
GLM 15 ST		LASER MEASURE Bosch Professional	Range: up to 50 ft

GLM 30 ST		LASER MEASURE Bosch Professional	Range: up to 100 ft
CN		DISTANT MEASURE	40m
NM		ELECTRIC SUGARCANE JUICER	
NM		MANUAL CHIPS CUTTER	
MW		CHAFF CUTTER	POWERPAK BRAND 2BLADE PETROL ENGINE/ELECTRIC MOTOR
MW		CHAFF CUTTER	POWERPAK BRAND 3BLADE PETROL ENGINE/ELECTRIC MOTOR

WYS18-BS500E-A AD		LAWN MOWER	ENGINE :B&S 500E SERIES DISPLACEMENT:140CC RATED POWER:2.6KW CUTTING WIDTH: 460MM GASOLINE ENGINE
HKBC-002 AD		4 IN 1 BRUSH CUTTER	PROFESSIONAL BRAND INCLUDES :TILLER,BRUSH CUTTER,WEEDER, RICE HARVESTER .
PG0105202 VV		3 in 1 BRUSH CUTTER PRESCOTT	Engine:1E44F-5B Engine type:2 stroke Displacement:52CC Rated Power:1.75kw 7000r/min Idling Speed:3000r/min Fuel Tank capacity:1200ml
AIXBC-52 MW		BRUSH CUTTER	BRAND NAME:MOON MOTOR:2.2KW/4HP SINGLE CYLINDER AIR COOLED TWO STROKE DISCHARGE:52CC
HKBC-001 AD		BRUSH CUTTER	HAWK KING BRAND
425LC AD		SPRAYER	SPRAYING AGENT TANK : NOMINAL VOL-15L (3.9 GAL) MAX FILL VOL:13L (3.4 GAL) PUMP SYSTEM:PISTON PUMP PRESSURE TANK VOL:1.3L SPRAY TUBE(PVC): 500MM PRESSURE HOSE:1300MM(51")
AC767 AD			AICO BRAND REVOLUTION :6500-7500R.P.M PRESSURE:15-25KG/CM2 DISCHARGE:7-10 L/MIN

TWPS101 VV		AUTOMATIC PRESSURE SWITCH	Staring pressure:1.5bar Max rated current:10A Max allowable pressure:10bar Rated voltage:220V-240V Frequency:50/60HZ Joint screw:inlet G1"male+outlet:G1"female Protection Degree:IP65.
THT109102 VV		Hydraulic bottle jack	Hydraulic bottle jack, 10Ton With safety valve Min. height: 230mm Max. height: 460mm Travel:230mm Net weight : 6.5kg Packed by color box
THT10821 VV		Hydraulic floor jack	Hydraulic floor jack, 2Ton Min. height: 140mm Max. height: 340mm Travel:200mm Net weight : 8.7kg Packed by color box
THT1651 VV		Chain block	Rating lift weight:5Ton Lift height:3m Number of load chain:2 Packed by wooden case
THT32321 VV		Folding hand riveter	Size:815mm,32" Applicable rivet size:3.2mm,4mm,4.8mm,6mm,6.4mm Packed by color box
THT111051 VV		Grease Gun	Heavy-Duty Grease Gun Taiwan Quality Capacity : 400CC / 14oz Loading way : 14Oz Cartridge / 400CC Bulk Working Pressure : 4500psi Burst Pressure : 10000psi Material : 1.2mm Steel tube + Aluminum-Cast Standard Accessory : 1pcs 12" High Pressure Flexible Nylon Hose 1pcs Metallic Bend Spout

AL		SILICON	BLACK/ WHITE/CLEAR
ST		AIR TOOLS KIT	5pcs set includes: 1ltr paint sprayer, tire inflator with pressure gauge and lock- on tire chuck, blow gun for cleaning, high pressure engine cleaner with cleaning solution reservoir and 15ft of 1/4" air hose with quick connects
AD		DELIVERY PIPE	2" X 100m
AD			3" x 100m
AD		DELIVERY PIPE	3"X 30M
ST		SUCTION PIPE	2" GREEN
ST			3" GREEN
F74-1030 CN		GLASS SUCKER	

CN		LADDER	Thickness of aluminum: 1.3-1.5mm Opening size: 320 x 47.6 x 8.4cm Folding size: 80.4 x 47.6 x 8.4cm Height between steps: 29.5cm Step no.: 11 Top step to ground: 320cm Loading Capacity: 150kg
ST		ELECTRODE HOLDER	900A
ST		WELDING CABLE	16mm
GX160 AD		ENGINE FUEL TANK	
N467980 AD		ARMATURE	For dewalt grinder
CN		ARMATURE	For grinder, drills and all other power tools
BK25 AD		CARBON BRUSH	For dewalt grinder

CN		GEAR	For grinder, drills and all other power tools
ST		SWIVEL COUPLER	
THT524101 VV		TIN SPIN	Size:10" Drop-forged steel Double dipped grip handle Packed by plastic hanger
THT59121 VV		MITRE BOX AND TENON SAW	Plastic mitre box with back saw 1pcs plastic mitre box Size:300×140×80, thickness:20mm 1pcs back saw Size:300mm/12" Double Color Handle
THT661301 VV		CHALK LINE REEL	Chalk line reel Length: 30m With 1 bottle chalk With 1 pcs spirit bubble Packed by double blister
TAT11601 VV		AIR TIRE INFLATING GUN	Air tire inflating gun max pressure: 12Bar(174PSI) Packed by single blister
TAC451321 VV		13mm Keyless chuck	13mm keyless chuck Chuck capacity:2-13mm Connection size:1/2"-20UNF Packed in color box
TAC451301 VV		13mm Key chuck	Chuck capacity:1.5-13mm Connection size:1/2"-20UNF Packed in color box

ST		CHUCK	13mm chuck with adapter
TAC7111151 VV		Polishing pad with flange	Diameter:115mm Material:Rubber M14x2 nut For wool polishing bonnet Packed by color box
TAC31031 VV		Cup wire brush with nut	75mm - 3 Wire dia:0.3mm Thread:M14X2 Packed in double blister
TAC34021 VV		Circular grinding wire brush	50mm wire:0.35mm Shank dia:6.35mm Packed in double blister
TAC34041 VV		Circular grinding wire brush	100mm Shank dia:6.35mm(1/4") Packed in double blister
TAC35061 VV		Circular grinding wire brush	150mm (6") arbor:25.4mm,Reduction ring:22.2mm,16.0mm Packed in color box



BACKBONE

BACKBONE CONSTRUCTION LTD. - KISUMU, KENYA.

TACSD12501 VV		250pcs Accessories of Mini Drill	76pcs Cutting disk 60pcs Sanding paper 1pcs Rubber grinding wheel 10pcs Grinding wheel with shank 4pcs Rubber polishing wheel 5pcs Felt wheels 1pcs Felt wheel point 1pcs Cloth wheel 39pcs Sanding band 6pcs Brush 7pcs Diamond bits 2pcs Engraving bit 4pcs mandrel bits 2pcs Sanding shank 6pcs Hss drill bits 4pcs Collets 1pcs Flap wheel 1pcs Wrench 1pcs Dressing stone 2pcs Polishing Compound 12pcs Gringing wheels 5pcs Cut off wheels fiberglass Packed by plastic box+label
2609390576 ST		POINTED CHISEL Bosch	Long Life, SDS-plus 250 mm
2609390394 ST		FLAT CHISEL Bosch	Long Life, SDS-plus 250 x 20 mm
AC		DEMOLITION CHISEL	mole pointed
AC			flat
AC		COMPRESSOR CHISEL	mole pointed



BACKBONE

BACKBONE CONSTRUCTION LTD. - KISUMU, KENYA.

AC		COMPRESSOR CHISEL	flat
2608595055 ST	 	METAL DRILL BITS Bosch	10pcs HSS-G, DIN 338 3 x 33 x 61 mm
2608595059 ST			10pcs HSS-G, DIN 338 4 x 43 x 75 mm
2608595062 ST			10pcs HSS-G, DIN 338 5 x 52 x 86 mm
2608595066 ST			10pcs HSS-G, DIN 338 6 x 57 x 93 mm
2608595072 ST			5pcs HSS-G, DIN 338 8 x 75 x 117 mm
2608595077 ST			5pcs HSS-G, DIN 338 10 x 87 x 133 mm
2608595081 ST			5pcs HSS-G, DIN 338 12 x 101 x 151 mm
2608680263 ST		HAMMER DRILL BIT Bosch	SDS-plus-1 6 x 100 x 160 mm
2608680270 ST			SDS-plus-1 8 x 100 x 160 mm
2608680271 ST			SDS-plus-1 8 x 150 x 210 mm
2608680273 ST			SDS- plus-1 10 x 100 x 160 mm



BACKBONE

BACKBONE CONSTRUCTION LTD. - KISUMU, KENYA.


2608680277 ST			SDS-plus-1 12 x 100 x 160 mm
2608680279 ST			SDS- plus-1 12 x 200 x 260 mm
2608680283 ST			SDS- plus-1 14 x 200 x 260 mm
TACSD4041 VV		HSS twist drill bits set for Cordless Screwdriver	4PCS HSS twist drill bit set Shank:1/4" hex Size:1.5,2.5,3.5,4.0mm Titanium finishing,fully ground High quality M2 HSS steel Fully ground drill bits
TAC190501 VV		SDS PLUS HAMMER DRILL BIT SET	5pcs SDS plus kit 6X110mm,8X110mm,10X110mm,10X160mm,12X160mm Packed in plastic box
2608595487 ST	 	SELF CUT SPEED SPADE BIT Bosch	Hexagon 16 x 152 mm
2608595489 ST			Hexagon 18 x 152 mm
2608595491 ST			Hexagon 20 x 152 mm
2608595492 ST			Hexagon 22x 152 mm
2608595494 ST			Hexagon 25 x 152 mm
2608595498 ST			Hexagon 32 x 152 mm
2608521039 ST		SCREW DRIVER BIT Bosch	10pcs double ended set

2608630033 ST		JIGSAW BLADE Bosch	5pcs T 111 C Basic for Wood
THT250603 VV		6PCS PRECISION SCREWDRIVER BIT	6 pcs precision screwdriver Included:PH1, PH0, SL1.4, SL2.0, SL2.4, SL3.0 Packed by plastic box+color box
TAC2411151 VV		SEGMENTED TURBO CUP GRINDING WHEEL	Diameter:115mm Blade width:20mm Arbor:22.22mm Packed by color box
TAC2411501 VV			Diameter:150mm Blade width:20mm Arbor:22.22mm Packed by color box
TAC25150801 VV		Abrasive grinding wheel TOTAL	Abrasive wheel size: 150x12.7x16mm Abrasive wheel grit: 80 grit For TOTAL item TBG15015 Packed by bulk
TAC25200361 VV			Abrasive wheel size: 150x12.7x16mm wheel grit: 80 grit item TBG15015 Abrasive For TOTAL Packed by bulk
2608602191 ST		DIAMOND CUTTING DISC for UNIVERSAL Bosch Professional	115 mm x 22,23 mm x 1,6 mm
2608602194 ST			180 mm x 22,23 mm x 2 mm
2608602794) ST			230 mm x 22,23 mm x 2,3 mm

CN		DIAMOND DISC	7" continuos
2608640853 ST		CIRCULAR SAW BLADE for OPTILINE WOOD Bosch	184 mm x 20 mm x 2,5 mm , 40T
2608640854 ST			184 mm x 20 mm x 2,5 mm , 60T
2608640894 ST			235 mm x 35 mm x 2,5 mm , 40T
2608640895 ST			235 mm x 35 mm x 2,5 mm , 60T
2608642202 ST		CIRCULAR SAW BLADE for MULTI MATERIAL Bosch	254 mm x 30 mm x 3,2 mm , 100T
CN		WOOD CIRCULAR BLADE	12" X 60T
CN			9" X 60T
TAC233523 VV		TCT SAW BLADE FOR ALUMINIUM	210mm(8-1/4") 60T,arbor:30mm 16mm and 25.4mm ring Suitable for mitre saw For TOTAL item TS42142101
2608603162 ST		CUTTING DISC BOSCH	9"
2608603161 ST			7"
2608603159 ST			4"

2608603184 ST		GRINDING DISC BOSCH	9"
2608603183 ST			7"
TAC430801 VV		HOLE CORE CUTTER	Core diameter:80mm 1pcs adaptor,110mm,SDS plus,1pcs 8X120mm drill bit Packed in color box
TAC430651 VV			Core diameter:65mm 1pcs adaptor,110mm,SDS plus,1pcs 8X120mm drill bit Packed in color box
PHSSA06 VV		SCREW DRIVER SET PRESCOTT	Slotted : 3X75 , 5X100, 5X150 Phillips : 3X75, 5X100, 6X125
TACSD30181 VV		18PCS T-handle wrench screwdriver set TOTAL	9pcs 6.35x25MM CR-V screwdriver: bitSL4,SL5,SL6,PH1,PH2,PH3,PZ1,PZ2,PZ3 1PC 5X100MM bit holder with strong magnetic 1PC T-handle Ratchet wrench 1PC 4- 6mm(25mm)adaptor 6PC 1/4" socket: 5,6,7,8,9,10 Packed in plastic box
PHSS181 VV		VDE SCREW DRIVER SET PRESCOTT	Slotted:0.5*3.0*75mm0.8*4.0*100mm 1.0*5.5*125mm 1.2*6.5*150mm Phillips:PH0*75mm PH1*100mm PH2*100mm Voltage test screwdriver 140mm CE 200-250V
THT91832 VV		3PCS WOOD FILE SET TOTAL	Size:8"/200mm, T12 Steel Flat wood file 1pcs Half round wood file 1pcs Round wood file 1pcs Packed by double blister

ST		HEX KEY	9pcs set long series 10mm 1.5mm -
ST			9pcs set short series 10mm 1.5mm -
THT106192 VV		HEX KEY TOTAL	9pcs hex key set(L) material: Cr-V heat treatment and chrome plate size: 1.5-10mm extra long arm packed by double blister
THTGP341 VV		GEAR PULLER 3 JAW TOTAL	Size:4", 3 Jaws Surface treatment : zinc-plated Range of application:20-120mm
TOC1804 VV		Charger TOTAL	Suitable for TOTAL 18V cordless drill TD318104
TOC1203 VV			Suitable for TOTALTOOLS 12V cordless drill TD312103
TSP9201 VV	 100% NEW PP	Welding mask TOTAL	Welding mask Material:100% PP Glass size:108*50*3mm, movable type glass 1 pcs clear protection glass Packed by carton box
TSP303 VV		WELDING GOGGLES TOTAL	Flip design with open-close locking positioning, easy to use. Flexible PVC body, indirect ventilation design. Inner lenses are clear, outer lenses adopt colored inorganic glass.
TSP304 VV		Safety goggle TOTAL	Conforms to ANSI Z87.1 and CE EN166; Full-view full-slice structure prevents UV and withstands impact; Fit to wearing the corrective glasses,also can be used as visitors glasses. Can defend against splash particles in the round Packed by double blister

TMT11301 VV		STEEL MEASURING TAPE TOTAL	Length & width:30mx12.5mm With metric and inch
TMT2601 VV		Spirit level TOTAL	Length : 60cm,Aluminum thickness:1mm
TMT2801 VV			Length : 80cm,Aluminum thickness:1mm
TMT21001 VV			Length : 100cm,Aluminum thickness:1mm
TMT21501 VV			Length : 150cm,Aluminum thickness:1mm
THT8414091 VV		9pcs paint brush set	9pcs paint brush set 3pcs 1" 2pcs 1.5" 2pcs 2.0" 1pcs 3.0" 1pcs 4.0" Wodden handle High quality bristles Packed by double blister and color card
THT85921 VV		Roller cover	Material:Acrylic yellow, Size:230mm/9" Fibre height:12mm Packed by plastic bag
ST		HACKSAW FRAME	Material: Harden flat steel Includes 1pc saw blade
ST		HACKSAW BLADE	

AD		POKER HEAD	Dynapac type
AEW300S/AEW500S AD		PRESSURE WASHER GUN	
APW550/650 AD			
TGTHPH52 VV		High Pressure Hose	Length:5 Meters Material:PVC Match with the Machinery of TGT1122,TGT1131,TGT1133
AEW300S/AEW500S AD		PRESSURE WASHER PIPE	
APW 550/650 PIPE AD			
AEW300/400S/550T AD		PRESSURE WASHER PUMP	
APW550/650 AD			
APW550 AD		PRESSURE WASHER REPAIR KIT	
AP650 AD			



BACKBONE

BACKBONE CONSTRUCTION LTD. - KISUMU, KENYA.

AD		PRESSURE WASHER NOZZLE TIP	Green
AD			Orange
AD			Red
AD			Black
AD			White
1001-1 CN		WALL LIGHT	
030-1 CN		HALF MOON WALL LIGHT	
5031 CN		FULL SMALL CEILING LIGHT	
5020 CN		FULL BIG CEILING LIGHT	
CN		LED FLOOD LIGHT	100W
CN			50W

CN		SWITCHES	1G 1W
CN		SWITCHES	2G 1W
CN			3G 1W
CN		D.P. SWITCH	
CN		SOCKETS	Twin Socket
CN			Single Socket
CN		LED STRIP LIGHT	50 meters per roll
CN		LED STRIP LIGHT CONTROLLER	

AF		WATER PROOFING POWDER	sikalite water proofing powder @1kg
CNCJ-80K		Tamping Rammer	Engine Type: Loncin 5.5Hp Impact Force(max):10kN Jumping Stroke(max)cm(in): 6.5(2.6) Size of Foot cm(in): 34.5x28.5 (13.6x11.2) Fuel Tank: 2.8L Impact number (number per minute): 450-650 handle on foot
CNP10		Plate Compactor	engine type: honda GX160 powerkW(hp): 3.6(5.5) weight kg(lbs): 62(137) frequency vpm: 5600 centrifugal force kN: 10.5 compaction depth cm(in): 20(8) travel speed cm/s(in/s): 40(16) efficiencycm²/hr(ft²/hr): 518(5578) plate size cm(in): 50x36(20x14)
CNP90		Plate Compactor	engine type: honda GX160 powerkW(hp): 3.6(5.5) weight kg(lbs): 88.5(195) frequency vpm: 4200 centrifugal force kN: 15 compaction depth cm(in): 30(12) travel speed cm/s(in/s): 38(119) efficiencycm²/hr(ft²/hr): 602(6476) plate size cm(in): 55X44(22x17)
CNQ16		Concrete Cutter	engine type: Honda GX390 power: 13HP max cutting depth cm(in): 14(5.5) blade size: 400mm depth adjustment: handle rotation driving: manual push water tank capacity: 35L
CNQ12		Concrete Cutter	engine type: Honda GX160 power: 5.5HP max cutting depth cm(in): 11(4.3) blade size: 350mm depth adjustment: handle rotation driving: manual push water tank capacity: 12L

CN-350C		Masonry & Stone Saw	motor voltage:220v power: 3.0kW 2800rpm 50Hz cm(in): 2.54(1)	rated blade speed: blade size:350mm max cutting depth cm(in):12.5(5) max cutting length cm(in): 120(47) arbor size weight kg(lbs): 120(265)
CN-350F		Masonry & Stone Saw	motor voltage:220v power: 3.0kW 2800rpm 50Hz size cm(in): 2.54(1)	rated blade speed: blade size:350mm max cutting depth cm(in): 11(4.3) max cutting length cm(in): 80(31.5) arbor weight kg(lbs): 76(168)
CNYL641		Walk Behind Vibratory Roller	engine type: honda GX160 power kW(hp): 3.6(5.5) weight kg(lbs):200(441) starting mode: hand starting travel speed m/hr: 3000 drive type: static hydraulic drive vibration type: mechanical static load N/cm: 40 nominal amplitude: 0.6mm vibratory frequency: 70Hz	
CNYL642		Walk Behind Vibratory Roller	engine type: honda GX390 power kW(hp): 8.2(13.0) weight kg(lbs):580(1279) starting mode: electric starting with battery travel speed m/hr: 4000 drive type: static hydraulic drive vibration type: mechanical vibratory frequency: 70Hz centrifugal force: 20kN water tank capacity:60L	
PT24		Power Trowel	engine type:Honda GX160 power kW(hp):3.6(5.5) weight kg(lbs): 50(110) rotor diameter cm(in): 58(22.8) finish blades cm(in): 23x12(9.0x4.7) millstone size cm(in):60(23.6) combo blade	

PT30		Power Trowel	engine type: Honda GX160 power kW(hp): 3.6(5.5) weight kg(lbs): 66(145) rotor diameter cm(in): 76(30) finish blades cm(in): 26x15(10.5X6) millstone size cm(in): 78.5(30.9) combo blade
PT36		Power Trowel	engine type: Honda GX160 power kW(hp): 3.6(5.5) weight kg(lbs): 78(171) rotor diameter cm(in): 91(36) finish blades cm(in): 35x15(14X6) millstone size cm(in): 97(38.2) combo blade
CNBS42		BLOCK SPLITTER	weight: 48kgs cm(in): (42) blade length max cutting height cm (in): 14(5.5) drive: manual
CNXB200		Scarifying Machine	electric motor power: 4kW voltage: 380v three phase working width cm(in): 20(8) working depth mm: 0-3 adjustable
CNGQ40		Steel Bar Cutting	three phase with clutch 50Hz diameter of cut steel bar (plain carbon steel mm): ≤ ϕ 40 diameter of cut steel bar (2-grade deformed steel bar mm): ≤ ϕ 32 speed numbers/min: 40 power kW: 3 motor speed rpm: 2880 cutting motor voltage V: 380



BACKBONE

BACKBONE CONSTRUCTION LTD. - KISUMU, KENYA.

CNGW40		steel Bar Bender	three phase automatic 50Hz specification of bending steel bar (plain carbon steel mm): $\leq \phi 40$ specification of bending steel bar(2- grade deformed steel bar mm): $\leq \phi 36$ bender rotating speed r/min: 8-11 motor power kW: 3 voltage V: 380 motor speed rpm:
CNGP20		Petrol Water Pump	loncin engine rated power kW(hp): 3.6(5.5) suction,distance, port diameter mm(in):50(2) discharge capacity m3/h:22 total head lift m(ft): 15(49.21) max suction head m(ft): 8(26.25) rotation speed rpm: 3600
CNVR		Concrete Vibrator	Honda GX160 dynapac type power kW(hp): 3.6(5.5)
CNVR			Loncin G160F dynapac type power kW(hp): 3.6(5.5)
CNDV		Electrical Concrete Vibrator	single phase voltage V: 220 frequency Hz: 50/60 power kW:1.5 speed rpm: 2840 vibrating poker length m: 4-6



BACKBONE CONSTRUCTION LTD. - KISUMU, KENYA.

		Vibrator Head	Dynapac Type
		Petrol Engine	Loncin G200F engine 196cc